

## PRODUCT DATA SHEET

<b>Low Tack Application Paper</b>	<b>APPLOW122091</b>
-----------------------------------	---------------------

<b>Description</b>	Low Tack Application Paper is standard weight saturated paper coated with a low tack latex rubber based adhesive designed specifically for pre- masking of medium to large sized die cut or computer cut vinyl lettering and graphics.
<b>Adhesive</b>	Rubber-based
<b>Colour</b>	White/Translucent
<b>Caliper facestock</b>	100-113 microns (4.0 -4.5 mils)
<b>Caliper facestock + adhesive</b>	125-138 microns (5.0 - 5.5 mils)
<b>Adhesion to Steel</b>	7-9 N/100mm (16 - 18 oz.)
<b>Tensile</b>	297 N/100mm (17lb./in)
<b>Elongation</b>	3-4%
<b>Tear Resistance</b>	50
<b>Shelf Life</b>	1 year
<b>Advantages</b>	<ul style="list-style-type: none"> <li>• Premask for medium to fine size vinyl graphics</li> <li>• All-purpose application paper for wet &amp; dry applications</li> <li>• Excellent for transferring graphics to banners</li> <li>• Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture</li> <li>• Store at 22 degrees C / 50-55 % RH</li> <li>• Standard roll sizes 1220mm x 91m</li> </ul>
<b>Other</b>	<ul style="list-style-type: none"> <li>• Removes cleanly &amp; easily following graphics applications</li> <li>• Works well with either wet or dry applications with no adhesive transfer</li> <li>• Can be slit to your requirements, please discuss with HVG Account Manager</li> </ul>

Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice.